



EN14351-1:2006 + A1:2010

Sierra Windows

Alders Way
Paignton,
Devon, TQ4 7QE
www.sierrawindows.co.uk



Edition: January 2013

DECLARATION OF PERFORMANCE

Tilt & Turn Window

TT(P22) – Profile 22 Tilt/Turn Window System
TT(24/7) – Swish Window & Door Tilt/Turn Window System

Intended use: not on escape route.

Essential performance characteristics

ID	Characteristics	TT(P22)	TT(24/7)					
1	Resistance to wind load (EN 12210)	<i>npd</i>	<i>npd</i>					
2	Watertightness (EN 12208)	<i>npd</i>	<i>npd</i>					
3	Air permeability (EN 12207)	<i>npd</i>	<i>npd</i>					
4	Dangerous substances ¹	<i>None</i>	<i>None</i>					
5	Load-bearing capacity of safety device	<i>None fitted</i>	<i>None fitted</i>					
6	Acoustic performance (EN ISO 140-3)	<i>npd</i>	<i>npd</i>					
7	Thermal transmittance ² (EN ISO 10077-1)	$\leq 1.6 \text{ W}/(\text{m}^2.\text{K})$	$\leq 1.6 \text{ W}/(\text{m}^2.\text{K})$					

BSI 0086 performed type test and issued KM 12887. ¹From statement issued by British Plastics Federation. ²By calculation using EN ISO 10077-1

Declaration of conformity: I, the undersigned hereby declare conformity with the above Directive(s) and Standard(s) as shown

Signature.....


Print: Martin Connor

Title: Divisional IMS Manager, Epwin Group Ltd (Building Products Division)